

ATLANTIC 1080

Atlantic 1080 Laminating systems are ideal for printing and finishing companies who want to do quality, mass production. Space saver, Atlantic 1080 completes perfectly the 91 (36") and














- Lamination, encapsulation, adhesive setting, mounting *40°c (104°F) recommended temperature for optimised results with cold films

Thermal films:

- Encapsulation with lamination films up to 250 microns thickness (10 mil)
- Encapsulation with opaque backing substrates
- Use of different type of film (finishing or texture) on top and bottom position
 - ** Same temperature adjustment for the upper and lower heating rollers
- *** Heat of the lower roller can be desactivated

Pivoting feeding tray facilitates easy loading of film rolls. Connected to a safety device installed in the machine, it provides maximum security to user while loading.







112 cm (44") wide printers.















Creative applications with Atlantic 1080

ATLANTIC 1080 Technical Specifications

Max. working width			1080 mm (42.5")	
Length of the roller		1100 mm (43.7")		
Diameter of the heating rollers			78 mm	(3,1")
Max. thickness of print + board			25 mm	(1")
Max. thickness of the film		250 micror	ns / side ((10 mil)
Adjustment and digital display of the heating rollers temperature		•	es from 2 8°F to 28	0 to 140°c 5°F
Digital display of the roller pressure			yes	
Upper and lower winding and unwinding spindles			yes	
Number of spindles delivered with the machine			4	
Maximum speed meters/min - (ft/m	in)		3 - (10)	
Reverse operation			yes	
Motor control pedal			yes	
Emergency stop button			2	
Stand mounted on self-locking cast	tors		yes	
Electrical print rewinding system			optional	
Power of the motor (W)			100	
Heating power (W)			3000	
Voltage		230V / 50	-60Hz sir	ngle phase
Amperes			14 amps	
Size of the machine on stand	L142 x C	76 x H137	7 cm - (56	6"x30"x34")
Weight of the machine kg - (Lbs)			184 - (40	5)
Size of the shipping crate	L180 x D1	05 x H100	cm - (71	"x42"x40")
Shipping weight kg - (Lbs)			227 - (50	0)
Made in France				
EC Certification				



KALA SAS - Parc de l'Ecotay 35 410 Nouvoitou - France

Tel.: +33 (0)2 99 37 64 64 - Fax: +33 (0)2 99 37 64 65 Internet: www.kala.fr - e-mail: info@kala.fr